

## CL520 | RizistalClean

### Description

Rizistal CL520 RizistalClean is a water-soluble floor cleaning detergent for use with our range of floor coating systems to meet after-care flooring needs.

RizistalClean can cope with most types of soiling within the Food, Chemical and Engineering industries, and other processing and manufacturing industries. It has the capabilities of removing a range of contaminations including the build-up of dirt, fats and greases on floors.

It is a safe-use, degreasing detergent being non-caustic, non-flammable, biodegradable and with a low odour.

RizistalClean can be used in steam cleaners, high-pressure washers, floor scrubbers and automatic washers.

### Storage

The product should be kept in its original unopened container until use.

The product should be stored in weather tight conditions, at temperatures between 10°C and 25°C, avoiding direct sunlight. Under these conditions this product has a shelf life of up to 12 months.

In the event of spillage or leaks, mop up bulk and dilute remainder to drain with water.

### Application

RizistalClean must be pre-diluted with water before use to give an adequate cleaning solution for the specific application.

Do not mix with any material other than water except where specifically directed.



For most cleaning requirements, dilutions between 2.5% and 5% are adequate, but the concentration required will vary according to the application and nature of the contamination.

RizistalClean can be safely used in steam cleaners, high-pressure washers and for cleaning by hand using brushes, cloths or low-pressure sprayers.

The following cleaning regime is the preferred method to maintain the appearance of a resin floor finish and provide a safer, cleaner working environment:

1. Apply the diluted cleaning detergent to the floor using a stiff polypropylene brush, mechanical floor scrubber or vacuum scrubbing machine.
2. Allow detergent sufficient contact time with dirt/grease deposits to ensure adequate removal of contaminant into suspension. For accumulated soiling, the length of time the detergent is in contact with the floor should be extended.
3. Manual scrubbing should then take place, using a stiff polypropylene brush, or mechanical scrubbing using a mechanical floor scrubber, such as STR rotary type scrubbers or



## CL520 | RizistalClean

a vacuum scrubbing machine, operated at a low to medium speed setting. For large flat floor areas, a vacuum-scrubbing machine fitted with nylon brushes is recommended, particularly for John Lord anti-slip systems. Additional cleaning may need to be carried out for floor areas where soiling has accumulated.

4. Ensure that all cleaning detergent residues are effectively removed by rinsing with clean water by means of a wet vacuum, vacuum-scrubbing machine or by squeegeeing excess into drains. Extra rinsing should be carried out where there is accumulated soiling.

### Safety

Avoid contact with the skin. Barrier creams or gloves should be used. Cleansing creams should also be used after accidental contact with the skin and / or washing with plenty of soap and hot water.

Accidental contact with the eyes should be treated by flushing with water and medical advice sought.

A detailed Material Safety Data Sheet is available which contains further advice.

### Ordering

Available from Rizistal online at [www.rizistal.co.uk](http://www.rizistal.co.uk).

All Rizistal products are sold subject to Rizistal's terms and conditions of sale.

For help and expert technical advice, please contact the Rizistal Support Team, who are backed by many years of experience within the flooring industry; [enquiries@rizistal.co.uk](mailto:enquiries@rizistal.co.uk).

Flash Point	None
Explosive Limits	None
Auto Ignition Temperature	None
Flammability	Not Flammable
Suitable for use with steam cleaner	Yes
Composition	Water Soluble, Slight Viscous Liquid
Application Concentration	2.5% - 10% according to application
Colour	Translucent Pink

All figures are measured and expressed as per laboratory conditions. Actual performance may vary from the above values depending on site conditions.

