# **RIZISTAL EC228 - HARDENER**

Page: 1

Compilation date: 14/08/2015

Revision date: 16/05/2017

Revision No: 3

# Section 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

### Product name: RIZISTAL EC228 - HARDENER

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Company name:	e: John L Lord & Son Ltd.	
	Unit 4	
	Park 66	
	Bury	
	Lancashire	
	BL9 8RZ	
	United Kingdom	
Tel:	+44 (0)161 764 4617	
Fax:	+44 (0)161 763 1873	
Email:	derrickhulett@john-lord.co.uk	

1.4. Emergency telephone number

# Section 2: Hazards identification

2.1. Classification of the substance or mixture		
Classification under CLP:	Acute Tox. 4: H302+H332; Aquatic Chronic 3: H412; Skin Corr. 1B: H314; Skin Sens. 1:	
	H317	
Most important adverse effects:	Harmful if swallowed or if inhaled Causes severe skin burns and eye damage. May	
	cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.	
2.2. Label elements		

# Label elements:

Hazard statements:	H302+H332: Harmful if swallowed or if inhaled
	H314: Causes severe skin burns and eye damage.
	H317: May cause an allergic skin reaction.
	H412: Harmful to aquatic life with long lasting effects.
Hazard pictograms:	GHS05: Corrosion
	GHS07: Exclamation mark



## **RIZISTAL EC228 - HARDENER**

**Page:** 2

Signal words:DangerPrecautionary statements:P260: Do not breathe dust/fumes/gas/mist/vapours/spray.P301+P312: IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.P280: Wear protective gloves/protective clothing/eye protection/face protection.P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomitingP302+P352: IF ON SKIN: Wash with plenty of water.P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.Rinse skin with water .

## 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

## 3.2. Mixtures

### Hazardous ingredients:

BENZYL ALCOHOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-859-9	100-51-6	-	Acute Tox. 4: H332; Acute Tox. 4: H302	30-50%

### 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

220-666-8	2855-13-2	-	Acute Tox. 4: H312; Acute Tox. 4: H302;	10-30%
			Skin Corr. 1B: H314; Skin Sens. 1:	
			H317; Aquatic Chronic 3: H412	

### M-PHENYLENEBIS(METHYLAMINE)

216-032-5	1477-55-0	-	Skin Sens. 1: H317; Skin Corr. 1B: H314; Acute Tox. 4: H302; Acute Tox. 4:	10-30%
			H332; Aquatic Chronic 3: H412	

## SALICYCLIC ACID

- 69-72-7 -	Eye Dam. 1: H318; Acute Tox. 4: H302	1-10%
-------------	--------------------------------------	-------

# Section 4: First aid measures

4.1. Description of first aid measures			
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.		
	Drench the affected skin with running water for 10 minutes or longer if substance is still		
	on skin. Transfer to hospital if there are burns or symptoms of poisoning.		
Eye contact:	Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist		
	examination.		
Ingestion:	Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10		
	minutes. If unconscious, check for breathing and apply artificial respiration if necessary.		
	If unconscious and breathing is OK, place in the recovery position. Transfer to hospital		
	as soon as possible.		

# **RIZISTAL EC228 - HARDENER**

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

#### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

- **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- **Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

## **RIZISTAL EC228 - HARDENER**

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

## Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

**DNEL/PNEC** Values

DNEL / PNEC No data available.

### 8.2. Exposure controls

Ensure there is sufficient ventilation of the area.	
Self-contained breathing apparatus must be available in case of emergency.	
Impermeable gloves.	
Tightly fitting safety goggles. Ensure eye bath is to hand.	
Impermeable protective clothing.	

### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	Pale yellow		
Odour:	Amine-like		
Solubility in water:	Not miscible		
Viscosity:	dynamic at 25c - 200 mPas (ISO 3219)		
Boiling point/range°C:	>200c	Melting point/range°C:	Not determined
Flammability limits %: lower:	1.2 Vol %	upper:	13.0 Vol %
Flash point°C:	>100c	Autoflammability°C:	380c
Vapour pressure:	0.1 hPa	Relative density:	1.06 g/cm <sup>3</sup> (ISO 2811

# **RIZISTAL EC228 - HARDENER**

### 9.2. Other information

Other information: Product is not selfigniting. Not explosive

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### **10.6. Hazardous decomposition products**

Haz. decomp. products: In combustion emits toxic fumes.

### Section 11: Toxicological information

### 11.1. Information on toxicological effects

## Hazardous ingredients:

# **BENZYL ALCOHOL**

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

### Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH ING	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

# **RIZISTAL EC228 - HARDENER**

**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

#### Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Dispose of as normal industrial waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### Section 14: Transport information

14.1. UN number

UN number: UN2735

### 14.2. UN proper shipping name

Shipping name: 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE)

(M-PHENYLENEBIS(METHYLAMINE), ISOPHORONEDAMINE.)

### 14.3. Transport hazard class(es)

Transport class: 8

### 14.4. Packing group

Packing group: ||

# **RIZISTAL EC228 - HARDENER**

### 14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

# Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.
	H302+H332: Harmful if swallowed or if inhaled
	H312: Harmful in contact with skin.
	H314: Causes severe skin burns and eye damage.
	H317: May cause an allergic skin reaction.
	H318: Causes serious eye damage.
	H332: Harmful if inhaled.
	H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.