RIZISTAL RM50 - NATURAL - BASE & AGGREGATE MIX

Page: 1

Compilation date: 30/04/2015

Revision date: 16/05/2017

Revision No: 3

### Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name: RIZISTAL RM50 - NATURAL - BASE & AGGREGATE MIX

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Company name: John L Lord & Son Ltd.

Unit 4 Park 66 Bury

Lancashire BL9 8RZ

United Kingdom

**Tel:** +44 (0)161 764 4617 **Fax:** +44 (0)161 763 1873

Email: derrickhulett@john-lord.co.uk

# 1.4. Emergency telephone number

# **Section 2: Hazards identification**

# 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT

SE 3: H335

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

# 2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation. H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark



RIZISTAL RM50 - NATURAL - BASE & AGGREGATE MIX

Page: 2

Signal words: Warning

Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.
P312: Call a POISON CENTRE or doctor if you feel unwell.
P321: Specific treatment (see instructions on this label)

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

### 3.2. Mixtures

### Hazardous ingredients:

#### CRYSTALLINE SILICA

EINECS	CAS	PBT / WEL	CLP Classification	Percent
238-878-4	14808-60-7	-	STOT SE 3: H335	>90%

#### Section 4: First aid measures

# 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult doctor if irritation develops or

persists

Ingestion: Immediately seek medical advice. Gently wipe or rinse out the mouth with water.

Inhalation: Move the exposed person to fresh air at once. Get medical attention if any discomfort

continues.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

RIZISTAL RM50 - NATURAL - BASE & AGGREGATE MIX

Page: 3

# Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

# 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

# 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

RIZISTAL RM50 - NATURAL - BASE & AGGREGATE MIX

Page: 4

8.1. Control parameters

Workplace exposure limits: No data available.

**DNEL/PNEC Values** 

**DNEL / PNEC** No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be

impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.Eye protection: Safety glasses.Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Powder & Liquid Mix

Colour: Pale yellow

Odour: Characteristic odour

# 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

# 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

# 10.4. Conditions to avoid

Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

RIZISTAL RM50 - NATURAL - BASE & AGGREGATE MIX

Page: 5

# **Section 11: Toxicological information**

#### 11.1. Information on toxicological effects

### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

#### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### **Section 12: Ecological information**

# 12.1. Toxicity

Ecotoxicity values: No data available.

# 12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

# 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

# 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

# 12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

# Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal

company.

**NB:** The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# RIZISTAL RM50 - NATURAL - BASE & AGGREGATE MIX

Page: 6

# **Section 14: Transport information**

14.1. UN number

UN number: N/A

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: N/A

14.4. Packing group

Packing group: N/A

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

# Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

# **Section 16: Other information**

# Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.